

# Aqua Mix® Aqua Stain

## 1 Product Name

Aqua Mix® Aqua Stain

## 2 Manufacturer

Custom Building Products  
13001 Seal Beach Blvd.  
Seal Beach, CA 90740-2757  
Customer Support: 800-272-8786  
Technical Services: 800-282-8786  
Fax: 800- 200-7765  
Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

A concentrated translucent stain designed to change the color and enhance the natural texture of porous adobe clay tile. Aqua Stain for Saltillo is available in five designer colors: Adobe Red, Fresco Peach, Piso Blanco, Spanish Oak and Terra Cotta. May also be used as a pre-grout coating to protect porous adobe tile from grout staining when used a minimum of 2 hours before grouting. Allows moisture vapor transmission.

### Key Features

- Changes the color of clay tile
- Provides a translucent to opaque effect
- Simplifies maintenance

### Suitable Tile Types

- Saltillo and other high porosity Adobe clay tile
- Effective for interior and exterior applications

### Limitations to the Product

Previously applied sealers must be removed as Aqua Stain must penetrate into porous tile. Aqua Mix® Sealer & Adhesive Remover is recommended to remove existing sealers.

## 4 Technical Data

### Technical Properties Chart

Complies with all Federal EPA and SCAQMD standards for VOC



## 5 Instructions

### Application of Product

Read entire label before using. SHAKE WELL before using. TEST A SMALL AREA according to application instructions, with a 24-hour cure time to determine desired results. Allow new installations to cure 24 hours before applying Aqua Stain for Saltillo. Surface must be clean and free of existing sealers or coatings. Aqua Stain may be used undiluted if a darker stain is desired or diluted with up to 8 parts water for lighter, more translucent stain. Pre-dampen tiles with water. Select a small, manageable area of 4 to 6 ft (.35 M to .55 M) and apply Aqua Stain for Saltillo with a dense sponge or lint-free cotton towel from a shallow dish. For best results, apply to individual tiles by hand. Rub into the tile in a circular motion using as much or as little stain as needed to achieve the desired appearance from the test area. If too much stain is applied or streaking occurs, immediately rework the area with a clean, damp sponge or towel and simply rub out the area using small amounts of water. For both interior and exterior applications, use Aqua Mix® Seal & Finish Low Sheen to seal, protect the color, and provide a durable low-sheen finish. If used on an interior application, and a high-sheen finish is desired, apply Aqua Mix® Floor Shine & Hardener over the Seal & Finish Low Sheen.

Clean applicator tools with water after each use.

### Cleaning of equipment

Clean tools and hands with water before material dries.

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains urea monohydrochloride. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	065911	1 Pint (473 ml)	Piso Blanco
USA	065921	1 Pint (473 ml)	Spanish Oak
USA	065931	1 Pint (473 ml)	Terra Cotta
USA	065941	1 Pint (473 ml)	Adobe Red



# CUSTOM®

# Aqua Mix® Aqua Stain

---

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. Click for details and complete [warranty information](#).

## 8 Product Maintenance

Properly installed product requires no special maintenance.

## 9 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 40° F - 90° F (4° C - 32° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

### Related Products

Aqua Mix® Seal & Finish Low Sheen

Aqua Mix® Floor Shine & Hardener



# CUSTOM®

# Aqua Mix® Aqua Stain

---

## Coverage

SIZE	Min Coverage	Max Coverage
Pint (473 mL)	50 sq. ft. (4.6 M <sup>2</sup> )	400 sq. ft. (37 M <sup>2</sup> )

Depending on type of tile, porosity and texture of surface, method of application and dilution ratio.



# CUSTOM®