

# Aqua Mix® Ex-Treme®

## 1 Product Name

Aqua Mix® Ex-Treme®

## 2 Manufacturer

Custom Building Products  
13001 Seal Beach Blvd.  
Seal Beach, CA 90740-2757  
Customer Support: 800-272-8786  
Technical Services: 800-282-8786  
Fax: 800- 200-7765  
Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

A nonflammable, heavy-viscosity acidic cleaner designed to remove years of accumulated discoloration from air pollution or carbon buildup, stains from smoke, soot, red soil and rust. It is a safer alternative to traditional harsh acids.

### Uses

Unpolished natural stone, concrete pavers, masonry surfaces, ceramic, porcelain, grout, quarry, saltillo, terra-cotta, and other acid resistant tile and stone.

### Limitations to the Product

- Do not use on polished, acid-sensitive stone (such as marble and limestone)
- Do not allow product to come in contact with any non-recommended surface
- Do not mix with ammoniated cleaners, such as bleach, as harmful fumes will result
- Acids of all kinds may etch, lighten, or change the color of cementitious material, metallic glazes and some natural stones such as marble and limestone

## 4 Technical Data

### Technical Properties Chart

- pH 2-3
- Complies with all Federal EPA and SCAQMD standards for VOC

## 5 Instructions

### General Surface Prep

Test a small area according to application instructions to determine desired results.

### Application of Product

Read entire label before using. Remove loose debris. Pre-wet the surface with water and remove excess before applying solution. Mix Ex-Treme® as follows:

LIGHT BUILDUP: Mix 1 part cleaner to 4 parts water.

MODERATE BUILDUP: Mix 1 part cleaner to 2 parts water.

HEAVY BUILDUP: Use undiluted.



Liberally apply solution with paint roller, brush or sponge. Allow to dwell up to 30 minutes. DO NOT ALLOW SOLUTION TO DRY ON SURFACE. Apply additional solution if drying occurs. Agitate with scrub brush thoroughly rinse with clean water. For vertical surfaces a garden hose or high-pressure washer may be used to rinse area. Mop or wet vacuum dirty solution. Heavy buildup may require additional applications and a longer dwell time.

### Cleaning of equipment

Clean tools and hands with water before material dries.

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether PNB, oxalic acid, and glycolic acid. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	100991*	1 gal (3.8 L)	Bottle
Canada	C100991*	1 gal (3.8 L)	Bottle

\* Indicates a special order item

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. Click for details and complete [warranty information](#).



# CUSTOM®

# Aqua Mix® Ex-Treme®

---

## 8 Product Maintenance

Properly installed product requires no special maintenance.

## 9 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 40° F - 90° F (4° C - 32° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

### Related Products

Aqua Mix® Sealer's Choice® Gold – Rapid Cure Formula

# Aqua Mix® Ex-Treme®

---

## Coverage

SIZE	Min Coverage	Max Coverage	
1 Gal (3.78 L)	200 sq. ft. (19 M <sup>2</sup> )	1,000 sq. ft. (93 M <sup>2</sup> )	Depending on dilution.