

# Aqua Mix® Floor Shine & Hardener

## 1 Product Name

Aqua Mix® Floor Shine & Hardener

## 2 Manufacturer

Custom Building Products  
13001 Seal Beach Blvd.  
Seal Beach, CA 90740-2757  
Customer Support: 800-272-8786  
Technical Services: 800-282-8786  
Fax: 800- 200-7765  
Email: contactus@cbpmail.net  
custombuildingproducts.com



## 3 Product Description

A clear, durable floor finish that resists surface abuse and leaves a beautiful high-shine finish. May also be used for pre-grouting protection on unglazed porcelain and crackled glazes. Allows moisture vapor transmission.

### Key Features

- Protective finish over sealed surfaces
- No buffing required

### Uses

- SEALED Saltillo, Terra Cotta, Slate, Sandstone, Adobe and quarry tile.
- Effective for interior dry areas only.

### Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface.
- Do not use a large-pored sponge applicator.
- Do not dip applicator directly into product, as bubbling (or foaming) will occur.
- Not recommended for exterior applications or for use as a finishing product on glazed ceramic or glazed porcelain tile.
- Do not use around pools, showers, countertops or areas subject to standing water.
- Keep surface clean and dry to reduce possibility of slip-fall accidents.

## 4 Technical Data

### Technical Properties Chart

Complies with all Federal EPA and SCAQMD standards for VOC

### Technical Chart

Property	Test Method	Requirement	Typical Results
Stain Resistance	CTI-072	n/a	Good
pH			n/a
Darken Stone			No
Cure Time			24 Hours
Expected Wear			Up to 1 Year

## 5 Instructions

### General Surface Prep

Surface should be dry, clean and free of any existing coatings. Do not apply directly over silicone sealers, oil or wax based finishes. Aqua Mix® Sealer & Coating Remover will strip the surface and remove wax or old acrylic finishes. Floor Shine & Hardener can be applied over any Aqua Mix® sealer except Stone & Enhancer and Enrich N Seal. Test product in obscure area to ensure desirable results.

### Application of Product

Read entire label before using. If an Aqua Mix® sealer is used, allow sealer to cure a minimum of 24 hours unless otherwise indicated on sealer label. Unglazed surfaces must be sealed prior to using Aqua Mix® Floor Shine & Hardener. Surface must be clean, dry and sealed. Apply by pouring a small amount of product directly onto a sealed floor and spreading evenly with a sponge mop or paint pad applicator. Avoid overlapping and puddling. Two to three coats are recommended for a high shine. If 2 or more coats are applied, allow a minimum of 1 hour drying time between coats. Clean applicator tools with soap and water after each use. May be reapplied as needed to surface that is clean and dry.

### For Pre-Grouting Application

Apply over clean unglazed porcelain tile or crackled finish tile a minimum of 2 hours prior to grouting. Follow application procedures above. After grout clean-up, any remaining residue of Floor Shine & Hardener can be removed using Aqua Mix® Heavy Duty Tile & Grout Cleaner following product directions.

Unglazed surfaces must be sealed prior to using Aqua Mix® Floor Shine & Hardener.

### Drying Time

Ready for surface traffic 3 hours after final coat. Keep area dry for 12 hours. Achieves a full cure in 24 hours.

### Cleaning of equipment

Clean tools and hands with soap and water immediately after use.



# CUSTOM®

# Aqua Mix® Floor Shine & Hardener

## Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 40°F - 90°F (4°C - 32°C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements

Aqua Mix® AquaKleen™

Aqua Mix® AquaShield™ Cleaner & Resealer

## Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains dipropylene glycol monomethyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting and seek medical attention.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	040282-4	1 Qt. (946 ml)	Bottle
USA	040283	1 Gal. (3.8 L)	Bottle
Canada	C040282-4	1 Qt. (946 ml)	Bottle
Canada	C040283	1 Gal. (3.8 L)	Bottle

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. Click for details and complete [warranty information](#).

## 8 Product Maintenance

Use an appropriate TileLab® or Aqua Mix® neutral cleaner for routine cleaning.

## 9 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10 Filing System

Additional product information is available from the manufacturer upon request.

## Expected Wear

EXPECTED WEAR UP TO 1 YEAR

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear

## Related Products

Aqua Mix® Concentrated Stone & Tile Cleaner

Published Date: 6/28/2013



# CUSTOM®

# Aqua Mix® Floor Shine & Hardener

---

## Coverage

Depends on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

Size	Min Coverage	Max Coverage
1 Gallon (3.78 L)	800 sq. ft. (74 M <sup>2</sup> )	1,000 sq. ft. (93 M <sup>2</sup> )