

# Aqua Mix® Poulitice Stain Remover

## 1 Product Name

Aqua Mix® Poulitice Stain Remover

## 2 Manufacturer

Custom Building Products  
13001 Seal Beach Blvd.  
Seal Beach, CA 90740-2757  
Customer Support: 800-272-8786  
Technical Services: 800-282-8786  
Fax: 800- 200-7765  
Email: contactus@cbpmail.net  
custombuildingproducts.com

## 3 Product Description

A dual purpose, non-acidic stain remover. It is an absorptive clay that is designed to remove deep-set oil and grease stains without scrubbing. It is also a fine abrasive cleaning powder that removes stubborn surface stains and light grout haze.

### Key Features

- Effectively removes deep-set oil and grease stains
- Safe, nonacidic, abrasive cleaning powder
- Excellent cleaning additive

### Uses

All natural stone (such as granite, limestone, marble, slate, and travertine), porcelain, quarry, Saltillo, terra-cotta, cement pavers, masonry surfaces, and other porous tile and grout

### Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- Extreme care should be taken with dark marble (especially green), as it may be more sensitive to moisture
- Light abrasive action or high RPMs on the surface of some marbles may dull the high-polished finish

## 4 Technical Data

### Technical Properties Chart

Complies with all Federal EPA and SCAQMD standards for VOC

## 5 Instructions

### Application of Product

FOR REMOVING DEEP-SET OIL AND GREASE STAINS:

Read entire label before using. Mix Poulitice Stain Remover powder with water to form a thick, pliable paste. Quantity of Poulitice Stain Remover needed will depend on size of stain. Apply a 1/4" (6 mm) thick layer of paste directly over stain with at least a 1" (25 mm) overlap beyond edge of stain. Cover with plastic or wax paper. Poke a few very small holes in plastic cover to allow for minimum air exposure. Allow paste to stand on stain for 24 to 48 hours. Remove Poulitice Stain Remover with plastic spatula or plastic putty knife and wash off residue with clean water. Repeat procedure if necessary. If area darkens from absorbed moisture, it should dry completely within 2 to 4 days.

FOR REMOVING STUBBORN SURFACE STAINS AND GROUT RESIDUE ON ACID SENSITIVE STONE:



Read entire label before using. Protect surrounding areas from splattering to minimize cleanup. Pre-wet a manageable area of the surface with water, approximately 10 ft (1 M) and sprinkle Poulitice Stain Remover onto the area mixing into a thin slurry. If surface is vertical, mix slurry in a container and apply to pre-wet surface. Agitate by hand or with low RPM (300-750 RPM) buffer using a white nylon scrub pad. Keep surface wet throughout buffing process. Remove Poulitice Stain Remover solution with clean towels or sponge and rinse twice with clean water. A wet/dry vacuum may be used. Polish surface dry with clean, dry towels or buff with soft lambs wool pad. Rinse with clean water and buff dry with clean towels

NOTE: Poulitice Stain Remover is an excellent additive that will boost the cleaning power of many of the Aqua Mix® cleaners such as Phosphoric Acid Substitute, Heavy-Duty Tile & Grout Cleaner, and Stone Deep Clean.

### Cleaning of equipment

Clean tools and hands with water before material dries.

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains barium sulfate and silicic acid. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

## 6 Availability & Cost

Location	Item Code	Size	Package
USA	010861	3/4 Lb. (.34 kg)	Jar
Canada	C010861	3/4 Lb. (.34 kg)	Jar



# CUSTOM®

# Aqua Mix® Poultice Stain Remover

---

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. Click for details and complete [warranty information](#).

## 8 Product Maintenance

Properly installed product requires no special maintenance.

## 9 Technical Services Information

For technical assistance, contact Custom® Building Products.

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 40° F - 90° F (4° C - 32° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

### Related Products

Aqua Mix® Sealer's Choice® Gold – Rapid Cure Formula



# CUSTOM®

# Aqua Mix® Poultice Stain Remover

---

## Coverage

SIZE	Min Coverage	Max Coverage
1 lb (.45 kg)	35 sq. ft. (3.3 M <sup>2</sup> )	1,000 sq. ft. (93 M <sup>2</sup> )